

Fig.1




Fig.2




Fig.3




Fig.4




Fig.5

SEATING DEVICE COMPRISING A FORWARD-FOLDABLE BACKREST

CROSS-REFERENCES TO RELATED APPLICATIONS

[0001] This application claims the benefit of the French patent application No. 12 61917 filed on Dec. 12, 2012, the entire disclosures of which are incorporated herein by way of reference.

BACKGROUND OF THE INVENTION

[0002] The present invention relates to a seating device with reduced bulk, for example for an aircraft.

[0003] In the aeronautical sector, some so-called “low-cost” airlines seek to increase the number of passengers transported on each flight, and more particularly on short-haul links, in order to maximize the return on the use of the aircraft.

[0004] To that end, and by using the same aircraft or an aircraft of similar capacity, the number of seats in the cabin must be increased.

[0005] In all cases, this increase in the number of seats is achieved to the detriment of the comfort of the passengers.

[0006] In effect, to increase the number of cabin seats, the space allotted to each passenger must be reduced.

[0007] However, this reduced comfort remains tolerable for the passengers in as much as the flight lasts only one or a few hours.

[0008] According to a first solution aiming to increase the number of cabin seats, it is possible to reduce the seating width allotted to each passenger in order to place an additional seat in the width of the cabin.

[0009] This first solution has already been pursued, and it is now no longer possible to further reduce the seating width, particularly in economy class.

[0010] According to a second solution aiming to increase the number of cabin seats, it is possible to reduce the distance available between two seats, that is to say the distance needed for the legs of the passenger.

[0011] This second solution has also been pursued hitherto, and it is difficult to continue to further reduce this distance between the seats because of the increase in the average size of the passengers.

[0012] According to a third solution aiming to increase the number of cabin seats, the design of the seats has to be optimized so that they present the smallest possible bulk.

[0013] This third solution has also been pursued by the engineers of the aeronautical sector.

[0014] While developing these three solutions aiming to increase the number of cabin seats, the engineers became aware that it was becoming increasingly difficult for the passengers to access the seating places located at the end of a row of seats, on the window side.

[0015] This access difficulty is mainly due to the reduced distance between two seats, and more specifically to the reduced distance between the seating of a first seat and the backrest of another seat situated in front of the first.

[0016] Also, the difficulty in accessing the seating places situated at the end of a row also stems from the presence of the armrests.

[0017] Also, to remedy such access difficulties, it is common practice, in an aircraft or in other people transport means, to provide seats with armrests and a seating that can be raised,

that is to say rotationally mounted so as to be able to be retracted upwards towards the backrest of the seat.

[0018] This known solution meets its limits when seeking to increase the number of seats in an aircraft cabin.

[0019] In practice, despite the many enhancements made to the aircraft seats, the retracted-up seating still has a certain thickness which remains cumbersome for access to the seating places situated at the end of a row, on the window side.

[0020] Furthermore, since the backrest of the seats with raisable armrests and seating remains fixed, it does not make it possible to free up any access to the seating places situated behind.

SUMMARY OF THE INVENTION

[0021] Thus, the present invention aims to mitigate the drawbacks of the prior art.

[0022] To this end, the invention proposes a seating device with reduced bulk for an aircraft.

[0023] This seating device comprises a support supporting a seating and a backrest, and this seating device can assume different configurations of use offering a seating place, as well as a retracted configuration offering a reduced bulk.

[0024] Also, this seating device is characterized in that its backrest describes a circular translational movement towards the front and upwards of the device when the seating device is brought to the retracted configuration.

[0025] By virtue of these kinematics, the backrest makes it possible to widen the access to the seating places situated behind when the seating device is in the retracted configuration.

[0026] It also becomes possible, by virtue of this particular mobility of the backrest, to further reduce the distance between different rows of seating devices in an aircraft cabin.

[0027] By virtue of the circular translational movement towards the front and upwards of the device when the seating device is retracted, the backrest is located in the vertical extension of the support when the seating device is in the retracted configuration.

[0028] Furthermore, the seating rotationally tilts so that its front end is moved downwards and towards the rear, and its rear end is moved upwards and towards the front when the seating device is retracted.

[0029] Thus, the seating is located between the backrest and the support, substantially in the vertical extension of these two elements, when the seating device is in the retracted configuration.

[0030] To obtain these movements of the backrest and of the seating, the seating and the backrest of the seating device are mounted on a deformable parallelogram.

[0031] In more detail, the deformable parallelogram comprising a front stay and a rear stay linked by a top stay and a bottom stay, the front stay and the rear stay are formed respectively by the support and by the backrest, and the seating is fixed to the top stay of the deformable parallelogram.

[0032] In order to reduce the bulk of the seating device in the retracted configuration and to reduce the distance needed to accommodate the legs of the passengers between two rows of seating devices, the seating takes the form of a motorcycle-type saddle.

[0033] Still with a view to reducing the bulk of the seating device in the retracted configuration, the backrest takes the form of a simple lumbar support held at the end of an arm.

[0034] Furthermore, the seating can offer a rotational mobility about a vertical axis relative to the support, and the

support can incorporate means for adjusting the seating height, these features making it possible to indirectly reduce the distance needed between two rows of seating devices.

[0035] To add to the seating comfort of the passenger, the seating device comprises a raisable armrest with an arm rotationally mounted about an axis of the support.

[0036] Advantageously, this armrest comprises a support element for a forearm mounted on a slideway at the end of the rotary arm, which makes it possible to press the support element onto the arm to minimize the bulk of the armrest once the latter is raised.

[0037] The present invention also covers a seating structure comprising a bearing piece, preferably a tube, on which are fixed, side by side, a plurality of seating devices, as well as an aircraft comprising a seating device.

BRIEF DESCRIPTION OF THE DRAWINGS

[0038] Other features and advantages will emerge from the following description of the invention, a description which is given purely as an example, in light of the appended drawings in which:

[0039] FIG. 1 is a perspective view of a seating structure comprising a plurality of seating devices, this view illustrating the invention,

[0040] FIG. 2 and FIG. 3 are schematic views respectively representing a seating device in the seating configuration and in the retracted configuration, these views illustrating the invention,

[0041] FIG. 4 is a side view of a plurality of rows of seating devices, this view illustrating the invention,

[0042] FIG. 5 is a perspective view from above of a plurality of rows of seating devices, this view illustrating the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0043] As illustrated in FIG. 1, the present invention relates to a seating device 10 with reduced bulk.

[0044] This seating device 10 is particularly intended for use in an aircraft cabin to receive a maximum number of passengers 12.

[0045] Obviously, this aeronautical application is non-limiting, and the seating device 10 according to the invention could perfectly well be used in other transport means in which the aim is to transport a maximum number of passengers, such as coaches or trains.

[0046] As is known, the seating device 10 comprises a support 14 supporting a seating 16 and a backrest 18.

[0047] According to the invention, the seating device 10 can assume different configurations of use offering a seating place, such as that illustrated by FIG. 2, and a retracted configuration offering a reduced bulk, this retracted configuration being illustrated in FIG. 3.

[0048] More precisely, a configuration of use of the device 10 offers a substantially horizontal seating 16, the different configurations of use being linked to the height adjustment and to the rotational adjustment of the device 10 about a vertical axis, as detailed later.

[0049] Thus, when the seating device 10 is brought to the retracted configuration, its backrest 18 is moved towards the front F of the device 10.

[0050] By virtue of this movement towards the front F, the backrest 18 makes it possible to free up access to the seating places situated at the rear R of the device 10.

[0051] More specifically, the backrest 18 describes a circular translational movement TC towards the front F and upwards U of the device 10 when the seating device 10 is brought to the retracted configuration.

[0052] "Circular translation" should be understood to mean that the invention intends the backrest 18 to describe a planar movement such that all the points of the backrest 18 have circular trajectories of the same radius but of different centers.

[0053] This circular translational movement makes it possible to maintain the backrest 18 in the same substantially vertical position regardless of the configuration assumed by the device 10.

[0054] Thus, regardless of the configuration assumed by the device 10, the backrest 18 provides the passenger with a lumbar support.

[0055] "Vertical" should be understood to mean a direction that goes from the bottom D of the device 10 to the top U of the device 10, and "horizontal" should be understood to mean a direction that goes from the rear R of the device 10 to the front F of the device 10.

[0056] Preferably, the backrest 18 describes a circular translational movement TC in a median plane PM of the device 10, the median plane PM separating the device 10 into two halves, right and left.

[0057] By virtue of this particular movement TC, the backrest 18 is located substantially in the vertical extension of the support 14, which reduces the bulk E of the device in the retracted position.

[0058] Still by virtue of this circular translational movement TC, the backrest 18 is moved away from the support 14 to allow the seating 16 to be retracted.

[0059] In practice, according to the invention, the seating 16 rotationally tilts RT about an axis 20 of the support 14 so that its front end 22 is moved downwards D and towards the rear R of the device 10, and its rear end 24 is moved upwards U and towards the front F of the device 10 when the seating device 10 is brought to the retracted configuration.

[0060] By virtue of this rotation RT, the seating 16 is located between the backrest 18 and the support 14 when the seating device 10 is in the retracted configuration, which reduces the bulk E of the device in the retracted position.

[0061] To minimize this bulk E of the device in the retracted position, the seating 16 is located partially in the vertical extension of the backrest 18 and of the support 14 when the seating device 10 is in the retracted configuration.

[0062] Preferably, the seating 16 describes its rotational movement RT in a median plane PM of the device 10, the axis of rotation 20 being at right angles to the median plane PM.

[0063] In a preferred arrangement of the seating device 10, the seating 16 and the backrest 18 of the seating device 10 are mounted on a deformable parallelogram 26.

[0064] This deformable parallelogram 26 makes it possible to obtain, mechanically and in a compact manner, the specific movements of the seating 16 and of the backrest 18 described above.

[0065] This deformable parallelogram 26 comprises a front stay 28 and a rear stay 30 linked by a top stay 32 and a bottom stay 34.

[0066] More specifically, the front stay 28 is linked by a top front hinge 36 to the top stay 32, the front stay 28 is linked by a bottom front hinge 38 to the bottom stay 34, the rear stay 30

is linked by a top rear hinge **40** to the top stay **32**, and the rear stay **30** is linked by a bottom rear hinge **42** to the bottom stay **34**.

[0067] In a preferred arrangement of the seating device **10**, the front stay **28** and the rear stay **30** are formed respectively by the support **14** and by the backrest **18**. There is thus obtained a very compact arrangement of the deformable parallelogram **26**, and consequently of the seating device **10**.

[0068] Still in a preferred arrangement of the seating device **10**, the seating **16** is fixed to the top stay **32** of the deformable parallelogram **26**.

[0069] The axis **20** of the support **14** about which the seating **16** rotationally tilts RT is therefore the top front hinge **36** of the deformable parallelogram **26**.

[0070] In comparison to an assembly on a slideway, the deformable parallelogram **26** does not require any fixed guiding piece likely to remain behind the backrest **18** when the seating device **10** is in the retracted configuration.

[0071] Advantageously, the deformable parallelogram **26** comprises return means, such as a spring, for returning to the retracted configuration.

[0072] In addition to this arrangement of the device **10**, the invention provides for the seating **16** to take the form of a motorcycle-type saddle **44**, the shape of this saddle **44** being visible in FIG. 1.

[0073] This saddle **44** comprises a front part **46** that is thinner than its rear part **48** and raised relative to the rear part **48**.

[0074] This saddle **44**, offering a better hold for a passenger **12** by virtue of its raised front part **46**, makes it possible to raise the seating **16** further by comparison with the aircraft seats with a parallelepipedal seating.

[0075] By further raising the seating **16**, and as FIGS. 1 and 4 illustrate, the legs of the passenger **12** are less retracted and require less space in relation to the seat in front.

[0076] Despite this further raising of the seating, the passenger is seated, and not standing.

[0077] As FIG. 4 illustrates, in order to adapt the seating device **10** to passengers **12** of different morphologies, the support **14** incorporates adjustment means, such as a manually controlled spring cylinder system, for adjusting the seating height **H16**.

[0078] The seating height **H16** is defined between the ground **S**, for example the floor of an aircraft cabin, and the seating **16**.

[0079] The adjustment of the seating height **H16** indirectly makes it possible to reduce the necessary distance **DN** between two rows of seating devices **10**.

[0080] In practice, this adjustment enables each passenger to adapt the seating height **H16** to his or her morphology, and this avoids providing an excessive necessary distance **DN** for passengers of large size by avoiding having them seated too low.

[0081] To refine the comfort of the passenger **12**, the seating **16** can also offer a rotational mobility **MR**, for example by a few tens of degrees, about a vertical axis **A16** relative to the support **14**.

[0082] This rotational mobility **MR** of the seating **16** about a vertical axis **A16** also indirectly makes it possible to reduce the necessary distance **DN** between two rows of seating devices **10**.

[0083] In practice, the rotation **MR** of the seating **16** enables the passenger to find a more ergonomic position so that he or she does not have to feel too close to his or her

neighbor in front, and, this rotation **MR** also enables the passengers to move while being seated to free up the passage to the seating places situated close to the window.

[0084] According to the invention, the backrest **18** takes the form of a lumbar support **50** held at the end of an arm **52**.

[0085] In a preferred arrangement of the seating device **10**, the bottom part **54** of the arm **52** constitutes the rear stay **30** of the deformable parallelogram **26**.

[0086] As illustrated in FIG. 1, the lumbar support **50**, possibly padded, follows a curved profile in a transversal plane **PT** of the seating device **10** so as to closely follow the anatomy of the back of a passenger, the transversal plane **PT** separating the device **10** into two halves, top and bottom, and being at right angles to the median plane **PM**.

[0087] In a minimal but sufficient variant, the lumbar support **50** has a height **H50** of ten or so centimeters, and a thickness **E50** of a few centimeters.

[0088] This minimal variant of the lumbar support **50** obviously makes it possible to limit the bulk **E** of the seating device **10**, notably by comparison with the aircraft seats with parallelepipedal backrest of the prior art.

[0089] To complement the comfort of a passenger **12**, and as illustrated in FIG. 4, the seating device **10** comprises a raisable armrest **56** with an arm **58** rotationally mounted about an axis **A58** that is fixed relative to the support **14**.

[0090] In a known manner, the raisable armrest **56** is mounted alongside the seating **16**. Also, in the case of a plurality of seating devices **10** forming a row, as FIG. 1 illustrates, a raisable armrest **56** is provided on each side of each seating device **10**.

[0091] Preferably, the axis **A58** of rotation of the arm **58** is perpendicular to the median plane **PM** of the device **10**.

[0092] However, the axis **A58** of rotation of the arm **58** is distinct from the axis **20** of rotation of the seating **16**.

[0093] The armrest **56** comprises a support element **60** for a forearm of a passenger **12** mounted on a slideway **62** at the top end **64** of the arm **58**.

[0094] Advantageously, the sliding of the support element **60** relative to the arm **58** defines the inclination **I** of the support element **60** relative to the arm **58**, and it makes it possible to keep the support element **60** in a substantially horizontal position.

[0095] Furthermore, the rotation of the armrest **56** in combination with the slideway **62** makes it possible to adjust the desired height **H56** of the armrest. Also, by rotating the arm **58** of the armrest **56** to a lower position, the slideway **62** makes it possible to keep the armrest **56** in a useable position situated close to the seating **16**.

[0096] Still by virtue of the slideway **62**, the support element **60** can be pressed onto the arm **58** to minimize the bulk **E56** of the armrest **56** when it is raised.

[0097] The present invention also covers a seating structure **66**, illustrated in FIG. 1, comprising a bearing piece **68**, preferably a tube, on which are fixed, side by side, a plurality of seating devices **10** so as to form a row **R1** of seating places.

[0098] Advantageously, the supports **14** of the different seating devices **10** are incorporated in this bearing piece **68** and the raisable armrests **56** are directly rotationally mounted on the bearing piece **68**.

[0099] The invention also covers an aircraft comprising a seating device **10** mounted in its cabin.

[0100] For example, an aircraft comprises a plurality of seating structures **66** mounted one behind the other in its

cabin so as to form a plurality of rows (R1, R2, R3, R4, R5, etc.) of seating places, as represented in FIG. 5.

[0101] To this end, the bearing piece 68 of each seating structure 66 is mounted on the floor 70 of the aircraft cabin via connecting rods 72, and a lateral arm 74 linking the bearing piece 68 to the structure of the aircraft in order to take up the torsional forces to which the latter is subjected.

[0102] Also, it can be seen that, by comparison with the aircraft seats of the prior art, the seating device 10 according to the invention offers a reduced bulk both when it is in use and when it is retracted.

[0103] Furthermore, it is possible to reduce the necessary distance DN between two rows of seating places while preserving the comfort of the passengers, both when they are seated and when they are accessing their place.

[0104] To give some idea, by virtue of the design of the seating device 10 according to the invention, it is possible to obtain four rows of seating places in the length in which only three rows of aircraft seats according to the prior art were able to be installed.

[0105] As is apparent from the foregoing specification, the invention is susceptible of being embodied with various alterations and modifications which may differ particularly from those that have been described in the preceding specification and description. It should be understood that I wish to embody within the scope of the patent warranted hereon all such modifications as reasonably and properly come within the scope of my contribution to the art.

- 1. A seating device with reduced bulk comprising:
 - a support supporting a seating and a backrest,
 - the seating device having a plurality of configurations of use offering a seating place and being movable to a retracted configuration offering a reduced bulk,
 - the backrest being arranged to move towards a front of the seating device when the seating device is moved to the retracted configuration,
 - the backrest describing a circular translational movement towards the front and upwards relative to the device when the seating device is moved to the retracted configuration.
- 2. The seating device with reduced bulk according to claim 1, wherein the seating rotationally tilts about an axis of the support so that its front end is moved downwards and towards the rear of the device, and its rear end is moved upwards and towards the front of the device when the seating device is moved to the retracted configuration.
- 3. The seating device with reduced bulk according to claim 1, wherein the seating and the backrest of the seating device are mounted on a deformable parallelogram.
- 4. The seating device with reduced bulk according to claim 3, wherein the deformable parallelogram comprises a front

stay and a rear stay linked by a top stay and a bottom stay, the front stay and the rear stay being formed respectively by the support and by the backrest, and the seating being fixed to the top stay of the deformable parallelogram.

5. The seating device with reduced bulk according to claim 1, wherein the seating takes the form of a motorcycle-type saddle.

6. The seating device with reduced bulk according to claim 1, wherein the backrest takes the form of a lumbar support held at the end of an arm.

7. The seating device with reduced bulk according to claim 1, wherein the seating has a rotational mobility about a vertical axis relative to the support.

8. The seating device with reduced bulk according to claim 1, wherein the support incorporates means for adjusting the seating height.

9. The seating device with reduced bulk according to claim 1, wherein the seating device comprises a raisable armrest with an arm rotationally mounted about an axis that is fixed relative to the support, the armrest comprising a support element for a forearm of a passenger mounted on a slideway at a top end of the arm.

10. A seating structure comprising a bearing piece on which are fixed, side by side, a plurality of seating devices so as to form a row of seating places, the seating devices each comprising:

- a support supporting a seating and a backrest,
- the seating device having a plurality of configurations of use offering a seating place and being movable to a retracted configuration offering a reduced bulk,
- the backrest being arranged to move towards a front of the seating device when the seating device is moved to the retracted configuration,
- the backrest describing a circular translational movement towards the front and upwards relative to the device when the seating device is moved to the retracted configuration.

11. An aircraft comprising at least one seating device mounted in its cabin, the seating device comprising:

- a support supporting a seating and a backrest,
- the seating device having a plurality of configurations of use offering a seating place and being movable to a retracted configuration offering a reduced bulk,
- the backrest being arranged to move towards a front of the seating device when the seating device is moved to the retracted configuration,
- the backrest describing a circular translational movement towards the front and upwards relative to the device when the seating device is moved to the retracted configuration.

* * * * *